

Neutrik NC3FXX - Ženski 3-pin XLR

Šifra: 6683
Kategorija prozivoda: Konektori
Proizvođač: Neutrik

Cena: 540,00 rsd

Features & Benefits

- Unique cage design of female contact for low contact resistance and high integrity
- Female connector with improved solid metal latch which is larger and easier to handle
- Improved chuck type strain relief provides higher pull-out force and makes assembly easier and faster
- Colored rings and boots available for coding or identification
- Rugged zinc diecast shell, longlasting and dependable
- Branded with unique hologram - guarantees genuine and authentic Neutrik product

Neutrik NC3FXX - Ženski 3-pin XLR

Neutrik NC3FXX

3 pole female cable connector with Nickel housing and silver contacts.
The next generation of the worldwide accepted standard of XLR cable connectors. The successor of the X series offers several new features which make it more reliable, easier to assemble and improves contact integrity as well cable strain relief.

- Female contact incorporates a solder barrier to prevent solder running into the contact mating area
- Additional ground spring contacts for better shell ground continuity
- Boot with polyurethane gland gives high protection to cable bending stresses
- Sleek and ergonomic design - valuable and handy
- Internal thread on shell is well protected against any damage

| Product | |
|------------------------------|-------------------------------|
| Connector Type | XLR |
| Gender | female |
| Electrical | |
| Capacitance between contacts | ≤ 4 pF |
| Contact resistance | ≤ 3 mΩ |
| Dielectric strength | 1,5 kVdc |
| Insulation resistance | > 2 GΩ (initial) |
| Insulation resistance | > 1 GΩ (after damp heat test) |
| Rated current per contact | 16 A |
| Rated voltage | 50 V |
| Mechanical | |
| Cable O.D. | 3.5 - 8.0 mm |
| Insertion force | ≤ 20 N |
| Withdrawal force | ≤ 20 N |
| Lifetime | > 1000 mating cycles |
| Wire size | max. 2.5 mm² |
| Wire size | max. 14 AWG |
| Wiring | Solder contacts |

| | |
|----------------------|----------------------------|
| Locking device | latch lock |
| Material | |
| Boot | Polyuretan |
| Bushing | Polyamide (PA 6 15% GR) |
| Contact plating | 2 µm Ag |
| Contacts | Nickel |
| Insert | Polyamide (PA 6.6 30 % GR) |
| Locking element | Zinc diecast (ZnAl4Cu1) |
| Shell | Zinc diecast (ZnAl4Cu1) |
| Shell plating | Nickel |
| Strain relief | Polyacetal (POM) |
| Environmental | |
| Flammability | UL 94 HB |
| Standard compliance | IEC 61076-2-103 |
| Protection class | IP 40 |
| Solderability | Complies with IEC 68-2-20 |
| Temperature range | -30 °C to +80 °C |