

Neutrik NC3MXX - Muški 3-pin XLR

Šifra: 06684

Kategorija proizvoda: Konektori

Proizvođač: Neutrik

Cena: 540,00 rsd



Neutrik // NC3MXX - XLR Male connector

XLR male connector for cable, 3 pins

Neutrik code = NC-3-MXX

The next generation of the worldwide accepted standard of XLR cable connectors. The successor of the X series offers several new features which make it more reliable, easier to assemble and improves contact integrity as well cable strain relief.

3 pole male cable connector with Nickel housing and silver contacts.

Features & Benefits

Male connector with improved locking recess without "window", more stringent housing increases durability

Improved chuck type strain relief provides higher pull-out force and makes assembly easier and faster

Boot with polyurethane gland gives high protection to cable bending stresses


Colored rings and boots available for coding or identification

Sleek and ergonomic design - valuable and handy

Rugged zinc diecast shell, longlasting and dependable

Internal thread on shell is well protected against any damage

Image not found or type unknown



Product	
Connector Type	XLR
Gender	male
Electrical	
Capacitance between contacts	≤ 4 pF
Contact resistance	≤ 3 m Ω
Dielectric strength	1,5 kVdc
Insulation resistance	> 2 G Ω (initial)
Insulation resistance	> 1 G Ω (after damp heat test)
Rated current per contact	16 A
Rated voltage	50 V
Mechanical	
Cable O.D.	3.5 - 8.0 mm
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wire size	max. 2.5 mm ²
Wire size	max. 14 AWG
Wiring	Solder contacts
Locking device	latch lock
Material	
Boot	Polyuretán
Bushing	Polyamide (PA 6 15% GR)
Contact plating	2 μ m Ag
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	Zinc diecast (ZnAl4Cu1)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Nickel
Strain relief	Polyacetal (POM)
Environmental	
Flammability	UL 94 HB
Standard compliance	IEC 61076-2-103

