

Neutrik NF2C B/2 RCA CINC

Šifra: 08158
Kategorija proizvoda: Konektori
Proizvođač: Neutrik

Cena: 3.000,00 rsd

No more disturbing noise and broken speaker cones
Neutrik unique chuck type strain relief
Sleek barrel with soft touch surface and coloured shrink sleeve

Title
NF2C-B/2
Connection Type
Profi
Gender
male
Electrical
Capacitance between contacts
≤ 7 pF
Contact resistance
>100G mΩ (inner)
Dielectric strength
1,5 kVdc
Insulation resistance
> 100 GΩ
Rated current per contact
16 A
Rated voltage
50 V
Mechanical
Cable O.D.
3.0 - 7.3 mm
Lifetime
> 2000 mating cycles
Wiresize
2,5 mm²
Wiresize
14 AWG
Wiring
Solder contacts
Material
Contact plating
5 μm Au over 5 μm Ni
Contacts
Brass (CuZn39Pb3)

Neutrik NF2C B/2 RCA CINC

Pair
of

professional `Phono Plug` (`RCA`- or `CINCH`- type)
- marked red and black.
Including 2 x 2 strain reliefs for cable O.D. 3.0
mm to 7.3 mm. Additional strain relief for cable O.D.
up to 8.0 mm available as accessory.

Features & Benefits

Makes ground before signal contact and breaks signal
before ground
Precisely machined to our demanding quality standards
Gold plated contacts
Improved ground solder lug for ease soldering

Insert
PBTP 20 % GR
Shell
Brass (CuZn39Pb3)
Strain relief
Polyacetal (POM)
Environmental
Flammability
UL 94 HB
Standard compliance
IEC 601-14
Protection class
IP 40
Solderability
Complies with IEC 68-2-20
Temperature range
-30 °C to +80 °C

Downloads

[Assembly Instruction - Profi](#)

[Assembly Instruction - Profi](#)

[Product Guide 2012, 03 Plugs+Jacks](#)

[Product Guide 2012, 03 Plugs+Jacks](#)

[Drawing NF2C](#)

[Drawing NF2C](#)

[Drawing NF2C](#)

[Drawing NF2C](#)