

## Neutrik NP2RX - Ugaoni 6.3mm mono jack

Šifra: 06685  
Kategorija proizvoda: Konektori  
Proizvođač: Neutrik

**Cena: 480,00 rsd**



<b>Product</b>	
Connector Type	Plug
Gender	male
<b>Electrical</b>	
Contact resistance	depends on mating connector mΩ
Dielectric strength	1 kVdc
Insulation resistance	> 2 GΩ (initial)
Insulation resistance	≥ 1 GΩ (after damp heat test)
Rated current per contact	≤ 15 A
<b>Mechanical</b>	
Cable O.D.	4 - 7 mm
Wire size	1 mm <sup>2</sup>
Wire size	18 AWG
Wiring	Solder contacts
RW / Straight	yes
<b>Material</b>	
Bushing	Polyacetal (POM) + PU
Contact plating	2 μm Ni (Su)
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Nickel
Strain relief	Polyacetal (POM)
<b>Environmental</b>	
Standard compliance	IEC 60603-11 / EIA RS-453
Solderability	Complies with IEC 68-2-20

Temperature range	-20 °C to +65 °C
-------------------	------------------