Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615 PIB: 106966344 E-mail: porudzbine@player.rs

NATIVE INSTRUMENTS KOMPLETE AUDIO 6 MK

NAJIVE: INSTRUMENTS KOMPLETE AUDIO 6 MK

Channel Premium Audio Interface

KOMPLETE SOUND BETTER

Šifra: 6604 Kategorija prozivoda: USB Zvučne kartice Proizvođač: Native Instruments

Cena: 19.080,00 rsd

KOMPLETE AUDIO 6 is a premium-quality 6-channel audio interface. It provides everything you need to record, play and perform music, with four analog ins/outs, digital in/out, MIDI and low-latency performance - all in a sleek, rugged metal casing. The two mic inputs are armed with high-end preamps while Cirrus Logic converters deliver pristine, transparent sound. Upgrade your setup with

KOMPLETE AUDIO 6 - because KOMPLETE sounds better.

The KOMPLETE AUDIO 6 package also includes KOMPLETE ELEMENTS, with over 1000 sounds and effects, plus software for recording, sequencing and DJing.

A SOUND DECISION

KOMPLETE AUDIO 6 lets you experience every facet of your sound, whether you're playing virtual instruments or recording audio. After all, if you're using MASCHINE or KOMPLETE Instruments and Effects, you're armed with an array of sounds in the highest-possible audio fidelity. KOMPLETE AUDIO 6 gives you the hardware to match.

Pristine sound doesn't happen by accident - it's the result of knowledge, experience and close attention to detail. KOMPLETE AUDIO 6 has been designed in-house by NATIVE INSTRUMENTS. From the custom, streamlined circuit design, through the hand-picked components to the analog volume knob on top of the unit - every part of the interface is designed to preserve signal clarity.

KOMPLETE CONNECTIVITY

KOMPLETE AUDIO 6 is designed to be flexible, with plenty of options for connecting mics, guitars, MIDI instruments or outboard gear:4 analog inputs:

2 balanced mic/line/instrument (XLR); plus 2 balanced line (1/4" TRS)

4 balanced analog outputs (1/4" TRS)

Digital stereo input and output (S/PDIF / RCA) for lossless signal transmission

MIDI in/out for master keyboard, MASCHINE or any third-party MIDI controller

Headphone output with independent level control and source switch

Completely USB powered, with an extra sturdy custom USB socket

New chips, new audio drivers and new circuitry ensure that latency is low, and the direct monitoring option provides 100% latency-free monitoring for recording guitars, vocals, or other live sources.

RECORD AND MONITOR

Other important recording features:

Low-latency performance for using virtual instruments and effects

High-quality pre-amps with individual gain controls

Direct monitoring for live, latency-free recording

Mono input switch for recording vocals, guitar or other mono sources

48V phantom power for using condenser mics and active DI boxes

15 status LEDs provide visual feedback for all signals and indicate clipping

SOFTWARE, SOUNDS AND SEQUENCER INSIDE

KOMPLETE AUDIO 6 includes a generous software package, so you can produce songs or mix tracks right out of the box:

KOMPLETE ELEMENTS - over 3 GB of inspiring instruments and effects CUBASE LE 5 - sequencer and recording software TRAKTOR LE 2 - DJ software \$30 / 25 € e-voucher - for KOMPLETE Instruments or Effects at the NI Online Shop*

Specification SYSTEM REQUIREMENTS

Windows Windows XP (latest Service Pack, 32 Bit), Windows Vista/Windows 7 (latest Service Pack, 32/64 Bit), Intel Pentium 4 2.4 GHz or Intel Core Duo or AMD Athlon 64, 2 GB RAM Mac Mac OS X 10.5 or 10.6 (latest update), Intel Core Duo, 2 GB RAM

SUPPORTED DRIVERS

ASIO Core Audio DirectSound WASAPI Monitor with 1024 x 768 screen resolution, USB 2.0, DVD drive **HARDWARE CHARACTERISTICS** DIMENSIONS: 2" (52 mm) x 6.3" (159 mm) x 4.8" (122 mm) WEIGHT: 1.9lb (850 grams) **Audio Converters** A/D Channels, D/A Channels 4, 4

D/A Channels 4, 4 Sample Rates 44.1, 48, 88.2, 96 kHz Bit Resolution 16, 24 Bit

Inputs 1/2

(A/D-D/A to Output*) Line Instrument Mic Input Impedance 44 kOhm, balanced 1 MOhm, unbalanced 3.4 kOhm, balanced Full-Scale Input Level @ max. Gain -4 dBu -9.7 dBu -36 dBu Maximum Input Level +14.3 dBu +8.4 dBu 0 dBu Gain -inf ... +15 dB -inf ... +21 dB +11 dB ... +47 dB Dynamic Range @ Unity Gain 98.3 dB (A) 98.3 dB (A) 98.0 dB (A) THD+N (Full-Scale Level, Unity Gain) 0.013 % 0.013 % 0.013 % Frequency Response(96 kHz), -1 dB 13 Hz - 42 kHz 12 Hz - 42 kHz 13 Hz - 45 kHz Equivalent Input Noise @ Max. Gain - - -127.5 dBu (A)

Inputs 3/4 (A/D-D/A toOutput*) Input Impedance 44 kOhm, balanced Full-Scale Input Level +12 dBu Gain -1 dB Dynamic Range 98.5 dB (A) THD+N (Full-Scale Level) 0.02 % Frequency Response (96 kHz), -1 dB 12 Hz - 43 kHz

Line Outputs (D/A) Full Scale Output Level @ Max. Volume +11 dBu Dynamic Range @ Max. Volume 102 dB (A) THD+N 1/2: 0.01%, 3/4: 0.02% Frequency Response (96 kHz), -1 dB 10 Hz - 45 kHz

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.