**logo**e not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

Five-Channel Analog Amplifiers

Setup Mic Input (Front)

Disci

E-mail: porudzbine@player.rs

ONKYOtTXIISR3736Blackwn

## ONKYO TX SR373 Black

Šifra: 11782

Kategorija prozivoda: AV Pojačala i Risiveri

135 W/Ch (6  $\Omega$ , 1 kHz, 1% THD, 1 Channel Driven)

Proizvođač: Onkyo

Cena: 33.480,00 rsd

Discrete high-current amps love music: use Bluetooth® wireless technology to stream any music playing on your phone, tablet, or laptop in moments. Connect all your gear (from network players to vintage consoles) to the TV via one HDMI® cable for a clutter-free install. Easy to use and with heaps of muscle, the TX-SR373 is an affordable way to get cinema sound at home.

### **Amplifier Features**

	High-Output Power Supply	
Processing Features  HDMI Support for 4K/60 Hz, 3D, Audio Return Channel, DeepColor™, x.v.Color™, and LipSync	Dolby® TrueHD and DTS-HD Master Audio™ Decoding	192 k
	SACD Playback via HDMI (2.8 MHz, 2 Channels)	Direc
Connection Features		
4 HDMI Inputs and 1 Output with Audio Return Channel	USB Input for MP3/WMA/AAC Playback via USB Memory Devices	2 Con
	2 Digital Audio Inputs (1 Optical and 1 Coaxial)	3 Ana
	Subwoofer Pre-Out	Head

### **Perfect Movie Soundtracks at Studio Resolution**

The TX-SR373 is ready to decode Dolby® TrueHD and DTS-HD Master Audio™—the most popular lossless multichannel soundtrack formats common to Blu-ray Disc™. Experience authentic movie sound as the director intended.

### **HDMI®** Connects You to the Future

Connect your players with just one cable linking to the TV for clean AV unit installation. HDMI terminals pass the latest video formats to your display, including those supporting 4K/60 Hz, HDR, BT.2020, and HDCP 2.2. There's also an Audio Return Channel (ARC) for amplifying TV broadcasts.

### Amp Power Adds Thrills to Music, Movies, Gaming, and TV Programs

Discrete analog amps (not an all-in-one integrated circuit) deliver high instantaneous current to the speakers for dynamic audio reproduction. Controlled power is the cornerstone of Onkyo's amplification philosophy.

### **AccuEQ Room Acoustic Calibration**

AccuEQ sets essential speaker conditions such as distance, output, and crossover, and EQs for a clear and balanced audio image that's free from distortion caused by the acoustics of your listening space.

#### **Bluetooth® Wireless Technology**

Bluetooth® wireless technology can stream whatever's playing on your mobile device, laptop, or PC to the home cinema. Use Onkyo-original Advanced Music Ontimizer mode to enrich any compressed audio for a

more satisfying musical experience. (Streaming device not included)

# **Enjoy Music via USB Input**

Connect a compatible USB memory device filled with MP3, WMA, or AAC audio files to enjoy clear and powerful reproduction of your music. Quality D/A conversion and a selection of DSP listening programs further enhance sound to suit different kinds of music.

## **Easy Connection Guide Simplifies Setup**

Connections to speakers and external devices are clearly labeled and illustrated on the rear panel—the connection diagram is readable upside down to make things easy when you're leaning over the top of the receive

Spec:

Spec.	
Onkyo TX-SR373 Specifications	
AMPLIFIER SECTION	
POWER OUTPUT	(Front L/R / Center / Surround L/R) 135 W/Ch (6 $\Omega$ , 1 kHz, 1% THD, 1 Channel Driven)
THD+N (TOTAL HARMONIC DISTORTION + NOISE)	$0.06\%$ (20 Hz-20 kHz, 8 $\Omega$ , 1 Channel Driven, 50 W)
INPUT SENSITIVITY AND IMPEDANCE	200 mV/47 k-Ω (Line)
FREQUENCY RESPONSE	5 Hz-100 kHz/0 dB, -3 dB (Direct Mode)
TONE CONTROL	±10 dB, 100 Hz (Bass) ±10 dB, 10 kHz (Treble)
SIGNAL-TO-NOISE RATIO	106 dB (Line, IHF-A Network, 1 k $\Omega$ Shorted)
SPEAKER IMPEDANCE	6 Ω-16 Ω
VIDEO SECTION	
INPUT SENSITIVITY/OUTPUT LEVEL AND IMPEDANCE	Video 1.0 Vp-p $\pm$ 5%/75 $\Omega$ (Composite)
TUNER SECTION	
TUNING FREQUENCY RANGE	FM - 87.5 MHz-107.9 MHz AM - 530 kHz-1,700 kHz
FM/AM PRESET MEMORY	30 Stations
GENERAL	
POWER SUPPLY	AC 120 V~, 60 Hz
POWER CONSUMPTION	210 W
STANDBY POWER CONSUMPTION	0.3 W
DIMENSIONS (W X H X D)	435 x 168 x 326.5 mm
WEIGHT	8.0 kg
CARTON	
DIMENSIONS (W X H X D)	522 x 247 x 430 mm
WEIGHT	9.5 kg