logoe not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

Fax: +381 11 334 PIB: 106966344

E-mail: porudzbine@player.rs

RHONG AM 442D USBnown

In this digital

PHONIC AM 442D USB

Šifra: 9679

Kategorija prozivoda: Miksete bez Snage

Proizvođač: PHONIC

Cena: 27.480,00 rsd

age, the ability to record each and every thing you do is a valuable commodity. Whether it's a quick and dirty demo, a shiny new live recording or just some quick licks you've come up with on the fly, recording has never been as easy as it is with an AM USB mixer. The AM442D USB, AM642D USB and AM844D USB are new members of the AM family of mixing consoles, exhibiting the same awesome features and classic analog feel that these units

display, but with a few fantastic additions. A stereo USB recording interface makes the unit perfect for recording live events, practice sessions, studio jams and so on, without the headache that comes with complex recording setups. In addition to this, a versatile compressor function has also been built right into mono channels for smoothing out vocals and drums. With just an AM USB mixer, a modern computer and a tiny bit of talent, you'll be making quality recordings in no time!

Minimum Requirements [

Windows

Microsoft® Windows® XP SP3 / Windows Vista / Windows 7 / Windows 8 (x84 and x64)

At least Core 2 Duo processor or equivalent AMD Athlon processor

5400 RPM or faster hard disk drive (7200 RPM or faster with 8 MB cache recommended)

Available USB 2.0 port

Motherboard with Intel or VIA chipset

1 GB or more of RAM (2 GB recommended)

Macintosh

OS X 10.3.5 or later G4 or newer processor Available USB 2.0 port 1 GB or more of RAM

4-Mic/Line 4-Stereo 2 Group Mixer with DFX & USB Interface

4 Mic/Line channels with inserts and phantom power

4 stereo channels with 4-band EQ

2 aux sends, aux 1 with Pre/Post switch

2 true subgroups with Main L and R routing switches Solo feature on each input and output

Convenient stereo RCA I/O 2T input with level control

Rack-mounting kit included

Stereo USB audio interface for PC and Mac computers 3-band EQ with swept mid-range plus low cut on each mono channel

32/40-bit digital effect processor with 100 programs + tap delay

2 stereo aux returns with effect to monitor level control XLR connectors available on main L / R output Built-in switching power supply with universal connector, 100-240VAC, 50/60Hz