

PHONIC Powerpod K12 Plus - Aktivna mikseta - Mikseta sa snagom

Šifra: 9662

Kategorija proizvoda: Miksete sa Snagom

Proizvođač: PHONIC

Cena: 87.600,00 rsd

tear sustained during transit. Perfect for use in clubs, houses of worship, function halls, bars, and other settings requiring a moderately sized, highly portable powered mixer.

1000W 12 Input Powered Mixer with GEQ and DFX

2 x 500W / 4 ohms stereo power amplifier (bridgeable and patchable)

Two stereo line input channels with 3-band EQ

Stereo 7-band graphic EQ assignable to main or aux 1

Two 32-bit digital effect processors, each with 100 effects plus tap delay effects, test tones and foot switch jack

2 AUX sends, 2 EFX sends

PFL on each input and AFL on each output

Zone 2 output for side fill or another PA system

Molded protective cover to avoid scratching and marking when on the road

Rugged metal main chassis with integrated handle for increased versatility

Optional rack mounting kit, model name ER-K12 (sold separately)

PHONIC Powerpod K12 Plus - Aktivna mikseta - Mikseta sa snagom

Phonic's Powerpod K12 Plus powered mixer features a grand total of 12 input channels – each offering 3-band swept-mid EQ, gain control, and more – as well as a built-in power amplifier outputting up to a staggering 1000 Watts of shear power.

Encompassing two built-in digital effect processors, each featuring 100 mind-blowing effects, the K12 also offers a sturdy yet light-weight construction due to the switch from heavy transformers.

Moreover, it features a protective cover – protecting the surface from damage, dust and normal wear and

Eight mic/line input channels with 3-band swept mid-range EQ and inserts

Two stereo returns, each can be routed to AUX 1 & 2 sends (effect to monitor)

Onboard GEQ features feedback detection on all bands

Mono output with variable low pass filter from 60 Hz up to 160 Hz

Global +48V phantom power for mic inputs

Stand-by switch for playing music between sets

One professional speaker connector and two 1/4" phone jacks per channel for speaker connection

sPs Solid Phonic System enhancement circuitry

Mains power switchable between 115 VAC and 230 VAC