

PRO-JECT Essential III Red OM10 incl. MDF-High-Gloss-Platter

Šifra: 11910
Kategorija proizvoda: Gramofoni
Proizvođač: Pro-Ject

Cena: 43.080,00 rsd

bolji zvuk od prethodnika, a izbor između crvene, crne ili bele boje visokog sjaja dodaje stil adekvatan kvalitetu reprodukcije.
<https://www.eisa.eu/awards/pro-ject-essential-iii-flexi-range/?lang=sr>

One of the most obvious changes with the new model is in the use of an upgraded Acryl-IT E platter. Also available seperately, the Acryl-IT E offers an inert platform for your vinyl records to reduce the unwanted effects of resonance. Available for use with and without the supplied felt mat, the platter uses a stainless steel bearing in a bronze bushing with Teflon-lined bottom for liquid-smooth rotation. The overall sound result is an open, exciting sound that arrives at a foot-tapping tempo.

The Essential 3 uses the same 9V motor as its predecessor, but it's also the first to use a new integrated grounding link that dramatically reduces electrical interference to unprecedented low levels. The motor is a premium, synchronous AC design that's driven by a built-in signal generator, ensuring optimal speed stability and minimal resonances. The brand new aluminium pulley improves the performance and the appearance even further still.

The Essential 3 is pre-fitted with an 8.6" aluminium tonearm for its lightweight, rigid characteristics. The gimbal bearing assembly uses sapphire bearings to allow for smooth tracking across a record, and the supplied counterweight allows for a variety of premium pick-up cartridges to be installed. The tonearm is supplied with an Ortofon OM 10 cartridge installed. Superior to the Essential II's OM 5E cartridge, the OM 10 uses an elliptical profile and precision micro-mechanics to deliver a nice, full soundstage with plenty of impact.

The Essential 3 is a significant step forward for vinyl enthusiasts on a budget. The sound and the style have been pushed to new heights, all for a price that defies belief.

- TickHigh quality Acrylic-IT E platter

TickLow vibration synchronous motor

TickMain platter bearing made from stainless steel runs in bronze bushing with Teflon bottom

TickFactory fitted Ortofon OM10 cartridge

TickSpecial turntable feet for effective decoupling
- TickBelt drive mechanism with silicone belt

TickIntegrated motor control with DC power supply secures silent running

Tick8.6" aluminium tonearm with sapphire bearings

TickPre-mounted gold-plated RCA interconnect cable

TickLid included

Nominal Speeds	33 / 45 RPM (Manual)
Speed Variance	±0.70% (33rpm) / ±0.60% (45rpm)
Wow & Flutter	±0.21% (33rpm) / ±0.19% (45rpm)
Signal-to-Noise	-66dB

Effective Tonearm Length	8.6" (218.5mm)
Effective Tonearm Mass	8.0gr
Overhang	22.0mm
Pre-Fitted Cartridge	Ortofon OM 10
Replacement Stylus	Ortofon 10 Stylus
Power Consumption	4.5W
Dimensions (W x H x D)	420 x 112 x 330mm
Weight	5.0 kg