

logo not found or type unknown

Firma: Player Plus doo  
Adresa: Svetogorska 9  
Telefon: +381 11 3347 442  
Fax: +381 11 3347 615  
PIB: 106966344  
E-mail: porudzbine@player.rs

MARANTZ PM 6006 Silver Gold

## MARANTZ PM 6006 Silver Gold

Šifra: 11026  
Kategorija proizvoda: Integrisana Pojačala  
Proizvođač: Marantz

Cena: 53.880,00 rsd

ONKYO R N855-B

Image not found or type unknown

The PM6006 is an upgraded successor of the multi-award-winning PM6005. Of course, Marantz have retained the pre-amp and power-amp sections that exclusively feature discrete components not a single IC in sight of the signal path. The PM6006 is upgraded for peak current at the amplifier stage, which makes it possible to refine the sound for you in much more detail. You can connect this superb integrated amplifier directly to a vast range of digital sources and use its superior 24bit/192kHz high current CS4398 DAC to create an unbelievably high level of audio enjoyment with new media.

Furthermore, the unit includes now 2 optical and 1 coaxial digital inputs (an additional optical input from the predecessor, PM6005). And the complete digital section is fully shielded by an extra metal housing to ensure that the digital stage has no effect on the analogue signal. And of course all of the original features such as five-line audio input including phono, two-pairs of gold-plated speaker connections with the convenience of bi-wiring, and a remote handset are all still there. The lower impedance shielded Toroidal transformer, as well as customized components and unique Marantz HDAM modules care for powerful, dynamic and detailed original Marantz sound.

Integrated Current Feedback Amplifier with 2x 45W / 8 ohm rms	Further sound tuned with carefully selected components	Digital
	High quality DAC CS4398 and Marantz HDAM SA2	Fully
	Gold Plated Inputs/Outputs incl. Phono (MM) input	Marantz
	Toroidal Transformer and high quality customised components	High
	Available in black or silver-gold	

### Current Feedback Technology

#### Current Feedback Technology

Current Feedback amplification is a well known, Marantz' original circuit technology. The Current Feedback

amplifier  
technology  
fits  
perfectly  
with the  
high  
requirements  
set for  
Super  
Audio  
software  
providing  
wide-  
bandwidth,  
high-  
speed  
reproduction.  
The  
impedance  
at the  
Current  
Feedback  
point is  
limited  
resulting  
in a  
very  
low  
phase  
shift.  
Marantz  
receivers  
and  
amplifiers  
equipped  
with  
Current  
Feedback  
can  
keep  
the  
phase  
compensation  
via  
Negative  
FeedBack  
(NFB) to  
a  
minimum,  
resulting  
in high  
through-  
rate,  
excellent  
transient  
response  
and  
superb  
sonic  
transparency  
for the



Image not found or type unknown

AudioVisual Online

Image not found or type unknown

"Switching between the PM6006 and its predecessor, we notice the 6006's presentation is notably cleaner and clearer – more solid too particularly through the midrange."

Features

Channels	2
Current Feedback Topology	Yes
Phono EQ	Standard
Digital In: USB-B / optical / coaxial / USB-A	No / Yes / Yes / No
Sample Rate Digital In	192 kHz / 24-bit
DAC Chip	CS4398
HDAM Version	SA3, SA2
Power Transformer	Toroidal
High Grade Audio Components	Yes
Customised Components	Yes
Aluminium Extrusion Heat Sink	Yes
Balance / Bass / Treble / Loudness	Yes

Others

Linear Drive Power Supply	Yes
Linear Volume Control	Yes
Shottky Diodes	Yes
Source Direct	Yes

Inputs / Outputs

<b>Audio Inputs</b>	5
<b>Digital in: USB-B / optical / coaxial / USB-A</b>	No / Yes:2 / Yes / No
<b>Phono Input</b>	MM
<b>Audio Outputs</b>	1
<b>Gold Plated Cinch</b>	Yes
<b>Speaker A / B</b>	Yes
<b>Speaker Terminals</b>	Metal (Gold) Screw
<b>Number of Terminals</b>	4
<b>D-Bus</b>	Yes
<b>Headphone Out</b>	Yes

### Specifications

<b>Power Output (8 / 4 Ohm RMS)</b>	45 W / 60 W
<b>Frequency Response</b>	10 Hz - 70 kHz
<b>Total Harmonic Distortion</b>	0.08 %
<b>Damping Factor</b>	100
<b>Input Sensitivity: MM</b>	2.2 mV / 47 kOhm
<b>Signal to Noise Ratio: MM / MC</b>	83 dB / -
<b>Input Sensitivity: High level</b>	200 mV / 20 kOhm
<b>Signal to Noise Ratio: High level</b>	102dB(2V input)

### General

<b>Available Colours</b>	Black / Silver-Gold
<b>Metal Front Panel</b>	Yes
<b>Power Consumption</b>	155W
<b>Standby Consumption</b>	0.3W
<b>Auto Power Off</b>	Yes
<b>Detachable Power Cable</b>	Yes
<b>Remote Control</b>	RC003PMCD
<b>System Remote Function</b>	Yes
<b>Maximum Dimensions (W x D x H)</b>	440 x 370 x 105mm
<b>Weight</b>	7.6Kg