Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615 PIB: 106966344 E-mail: porudzbine@player.rs

MARANTZ PM7005 N1B

Šifra: 216 Kategorija prozivoda: Integrisana Pojačala Proizvođač: Marantz

Cena: 71.880,00 rsd

MARANTIZURM7005 NilBown

То

guarantee best sound quality, the PM7005 includes high-grade audio components, current feedback HDAMs and a high-speed instantaneous current power supply. It also comes with the same high grade speaker terminals as used in the PM8005 for the best possible speaker connectivity. The DACmode features optical and coaxial digital inputs as well as a USB-B port, which means you can directly connect your computer to the PM7005 and benefit

from its high-quality DAC CS4398 and its HDAM-SA3 module-equipped audio output stage for great audio performance. The amp operates as a soundcard for the computer and the USB-B port works in asynchronous mode and 'bit-perfect' to support not only 192kHz / 24bits but also the DSD 2.8MHz and 5.6MHz high-resolution audio. All this digital dazzle is at your fingertips so you can enjoy your digital media wherever you want. But because we also care about the sensitive analogue signal from other sources as well, we built-in the Analog Amp Mode – which simply switches off the digital section completely, enabling you to enjoy the purest analogue audio you can possibly imagine. Perfect for your vinyls.

Channels			2	
Digital in: USB-B / optical / coaxial			QnalgQnal	g©hægtædoont tigpætdyplertignpl
Current Feedback Topology				© nage not fou
Phono EQ: Standard / Current Feedback / Constant Curr	ent Feed	back		On digier/adjustance da
HDAM version		SA3, SA2		
Power Transformer: Toroidal / El				Image anget footrfd wrdt y
High Grade Audio Components				Ønage not fo
Customised Components				O nage not four
Symmetric PCB Layout				© nage not found
Aluminium extrusion heat sink				O nage not fo
Balance / Bass / Treble / Loudness			Ondgendgendge	dawtellynde tlynker wyder wyder
Linear Drive Power Supply				O nage not fou
Shottky diodes				O nage not found or ty
Input buffer amp (all inputs / CD only)				tm / a g earget frøtrfolum

Separate Solid Heat Sinks			O nage not fou
System block shielding: copper / metal / none			tm/a @e / ghinfagierfd ochrôcopr
Source Direct			O nage not found or type
Standby Mode			O nage not found or typ
Analog Mode		۵ د	nage not found or type
			5
Audio Inputs			
Digital in: USB-B / optical / coaxial		OnalgOnalg	@fræigtedcont:tdøpre:tdyrplertsynpl
Phono Input: MM / MC		O n <i>a</i> lgte	nagtefoot doointly pe typler
Audio Outputs			1
Gold Plated Cinch			Onage not found or
Speaker Terminal: Screw / Marantz / WBT	łm/a@e	SPKTrid	, pr ichyapyaeyupraktoforkwin dvorm typ
Number of terminals			2
D-Bus	Ønage	not found (or type unknown
Headphone Out			O nage not found or t
Power Output (8 / 4 Ohm RMS)	60 W /	80 W	
Frequency Response	5 Hz-100 kHz		
Total Harmonic Distortion		0.02 %	
Damping Factor		100	
Input Sensitivity: MM	2 mV / 47 kOhm		
Signal to Noise Ratio: MM / MC	8	85 dB / ⊦n	nage not found or type
Input Sensitivity: High level	200 mV / 20 kOhm		
Signal to Noise Ratio: High level	104 dB (2V inp	out)	
Available colors: Gold / Silver / Black / Silver-Gold		tm / atm	la Qa IgQnabber dogordogords
Metal Front Panel			
			O nage not found or
Power Consumption in W		170 W	

Standby Consumption in W			0.2 W	
Auto power off			O n a	age not found or ty
Detachable Power Cable				G nage not four
Remote Control	RC0032PMSA			
System Remote Function				Ø nage not fou
Maximum Dimensions (W x H x D) in mm		440 x 12	5 x 379	
Weight in kg			10	

mage not found or type unknown

Customized Components

On paper an electrical component might look excellent but the result may fall short of the combined design expectations. Marantz selects the appropriate components for the specific design application. In some cases it's simply not possible to use standard components that meet the high Marantz standards. These components will then be specially made for Marantz in close cooperation with the Marantz engineers.

L			
L		\backslash	
Ŀ			\backslash

HDAM SA3

Marantz developed its own discrete circuit boards to replace standard IC's. These HDAM's consists of discrete surface mount components with short mirror image L/R signal paths. Those devices are doing exactly the same thing as the Op-Amps, but outperform the regular IC Op-amps dramatically in terms of the Slew Rate and reduced noise level, resulting in a much more dynamic, accurate and detailed sound. Over the years Marantz developed different types of the HDAM to improve quality and to fit to the special requirements of a product category like CD or amplifier.

mage not found or type unknown

Shottky Diodes

A Shottky diode is a special type of diode with a very low forward-voltage drop compared to normal diodes. This lower voltage drop translates into higher system efficiency. Shottky diodes have very fast signal handling, can easily stay higher temperatures and are sensitive very low voltages.

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.