

## LEM Procon 2200 plus - Razglasno pojačalo

Šifra: 02031  
 Kategorija proizvoda: Razglasna Pojačala  
 Proizvođač: LEM



**Cena: 59.880,00 rsd**

<b>Power specifications</b>	
<b>EIA output power (1 kHz, THD 1%) Both channels</b>	8 ohms: 650W + 650W 4 ohms: 1.100W + 1.100W 8 ohms bridged: 2.200W
<b>Electrical specifications</b>	
<b>Input sensitivity</b>	0dB (0.775V)
<b>Input impedance</b>	10 kohms (balanced)
<b>Frequency response</b>	10Hz - 50kHz (-0,5dB)
<b>Voltage gain</b>	39 dB
<b>Slew rate</b>	22 V/ms
<b>Damping factor</b>	Higher then 400:1 @ 1kHz, 8 ohms
<b>Crosstalk</b>	-82dB (1kHz)
<b>S/N ratio</b>	-98dB
<b>Harmonic distorsion (THD)</b>	Lower then 0,1% (ref 20Hz -20kHz)
<b>Intermodulation distortion SMPTE</b>	Lower then 0,1% (SMPTE method, 60Hz & 7kHz, 400:1 ratio)
<b>General specifications</b>	
<b>Protections</b>	Power transformer thermal protection; short circuit protection; sensor for current on outputs; clip limiter on each channel; soft-start circuit (1000P to 2200P)
<b>Controls</b>	On/off switch, 21-detect input level control for each channel, Mode selector, Shield selector
<b>Indicators</b>	Power On: 1 red LED Bridge: 1 red LED Protect: 1 red LED Level: 2 x 5 LED meter Limit: 1 red LED

<b>Connections</b>	Input: 1 XLR-F + 1 1/4" jack in parallel for each channel Output: 2 binding post + 1 speakon for each channel (400-1500); 1 speakon for each channel + 1 speakon for Bridge output (1800-2200)
<b>Power supply</b>	See label on the apparatus
<b>Dimensions (W x H x D)</b>	483 x 88 x 456 mm / 19" x 3,46" x 17,95"
<b>Weight</b>	25 kg / 55,1 lbs

