

MARTIN WISMAN PROX 1600 - Razglasno pojačalo

Šifra: 06928
 Kategorija proizvoda: Razglasna Pojačala
 Proizvođač: Martin Wisman

Cena: 61.452,00 rsd

analog amplifier for professionals with best power/price ratio.

Features

Soft start-up, preventing the transient surge and reducing the disturbance to the power network

Adapting the MOSFET high speed voltage switching technology, reduces the wave distortion when switching the voltage.

Aluminum heat-sink with good quality & variable speed fans with low noise produce efficient ventilation and cooling effect. Enable the amp to work for a long continuous period without overheat protection.

Adapts safe& reliable input Combo and output Speakon connectors.

Stereo/parallel 8Ω	400W x2
Stereo/parallel 4Ω	600W x2

Stereo/parallel 2Ω	720W x2
Bridge 8Ω	1200W

Bridge 4Ω	1440W
THD+N	<0.1%

IMD	<0.1%
Frequency response	20Hz ~ 20 kHz

MARTIN WISMAN PROX 1600 - Razglasno pojačalo

Martin Wisman PROX 1600

Profesional power amplifier

PROX series power amplifiers represents the state-of-the-art in professional quality performance at an affordable price. Designed to deliver high levels of sustained power, extraordinary audio performance, and road-proven reliability. With oversized high-current toroidal transformers for greater 2 ohm power and H class output circuit you have ultimate

Working mode of Stereo, Bridge and Parallel can be chosen; the input signal's sensitivity also can be chosen from 0.775V, 1.0V, 1.44V. The amplification transistors adapt the complementary collecting design, fixing the amplification transistors directly on the heat sink: this lessens overheat of transistors and distortion; meanwhile extends the lifespan of transistors.

Limiter protection design for fast and sensitive current limiting and range limiting. Even when the signal over-range, the output of the amp still can maintain very low distortion. This will decrease the situation of burning the speakers when under overload or over-range.

Input Sensitivity	0.775V/1.0V/1.44V (stereo 8Ω)
S/N ratio	>100dB

Crosstalk	>70dB
Damping Factor	>300 (@8Ω)

Protection	Soft start up, DC fault, AC line fuse, thermal cut off, soft start, Automatic voltage limited
Connectors	Input: COMBO x 2; XLR link male x 2 Output: SPEAKON x 3

Power supply	230V ± 10% ~50/60Hz
Dimension	483 x 425 x 88mm (19", 2U)

Weight	18.2kgs
--------	---------