

logo not found or type unknown

Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

QED Reference Audio 40 1m


Šifra: 11476
Kategorija proizvoda: Hi-Fi Analogni kablovi
Proizvođač: QED

Cena: 17.880,00 rsd

QED Reference Audio 40 1m

"This kind of transparency is difficult for rivals to match"


image not found or type unknown



"Near total transparency that is the


mark of an award-winner."

image not found or type unknown




"Natural, organic way of making music that's wonderfully smooth"

image not found or type unknown




"Cannot be faulted for build, technical parameters, sound or value"

image not found or type unknown



"Very low power loss, across the audioband it's the perfect solution for high-end systems"

image not found or type unknown



"Outstanding, among the best"

Engineering pedigree

QED has been designing and engineering superior analogue and digital cables for more than 45 years, and its new Reference Audio 40 cable is informed by the results of the company's exhaustive research into cable design since 1995.

All-new Analoc2™ design

The Analoc2™ design still features low bulk, high purity copper connectors alongside low mass metal

barrels, but now cleverly substitutes high rigidity thermoplastic material for both the inner support structure and the cable strain relief to eliminate the detrimental effects of eddy currents. Although already smaller than in traditional bulk brass plugs, these unfavourable currents were still able to circulate weakly in the isolated metal body of the previous plug design. Now with the new material in place, these remnant resonant distortions are completely prevented from adversely affecting the information contained in the audio signal as it travels through the new plug.

To complete the RCA plug's Analoc2™ upgrade and to help combat the skin effect, the hollow, gold (or rhodium) plated, high-purity copper signal-pins are retained, while the effectiveness of the slip ring which locks in place the similarly plated, pure copper ground-terminal as the barrels are tightened, has also been improved.

Ferrite cord insulation

A Zn/Mn Ferrite jacket is used within the cordage to absorb very high frequency noise components outside of the audible band that have an adverse effect on the micro-timing of the audio signal. When measured at very high frequencies, Reference Audio 40 cables exhibit cleaner signal transmission than standard audio interconnects. Further protection for the Silver Plated 99.999% Oxygen Free Copper (SPOFC) conductors comes in the form of a low loss, low density, dielectric foam Polyethylene (LDPE) inner jacket that minimises

electrical energy loss in the cable insulation which can have a detrimental effect on the fidelity of the sound compared with cheaper PVC alternatives

Technical specification

Analoc2™ plug with inner high rigidity thermoplastic material

Silver Plated 99.999% Oxygen Free Copper (SPOFC) conductors with LDPE dielectric

Asymmetrical twisted pair geometry

OFC shield giving 100% electromagnetic screening

Zn/Mn ferrite Jacket

Gold plated updated QED Analoc2™ RCA plugs

Parallel Capacitance: 76 pF/m

Inductance: 0.37 μH/m

Loop resistance: 0.072 Ω/m

Dissipation Factor: 0.0059

OVERALL PERFORMANCE

Analoc
Image not found or type unknown

Analoc2™ Technology

QED Analoc2™ RCA plugs feature high-purity copper signal and ground connections supported by a new non-conductive low eddy current body. The hollow central pin eliminates the skin effect at high frequencies and the revised locking barrel design clamps the dual blade ground connection firmly to the RCA sockets for improved noise rejection. The all new Analoc2™ design cleverly substitutes high rigidity thermoplastic material for both the inner support structure and the cable strain relief to eliminate the distorting effects of eddy currents, which are always present in ordinary plugs where bulk brass is used instead

CGT
Image not found or type unknown

Complementary Conductor Technology

Complementary conductor geometry utilises two conductors of different diameters to carry the same audio signal. This has the effect of providing an alternative path for high frequency audio components which might otherwise become time smeared in a single audio pathway.

Ferrite Image not found or type unknown

Ferrite Insulation Technology

Like putting wooden wheels on a Ferrari, conventional RCA phono plugs have the potential to undo all of the hard work carried out by our carefully designed cordage. With Anamate and Analoc RCA plugs, the fidelity of the audio signal is maintained from start to finish.

WHAT THIS CABLE IS USED FOR

CONNECT YOUR:

DVD player
CD Player
DAC
Turntable

TO YOUR:

Receiver
AV Amplifier