Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

MARTIN RUSH Wizard - Skener

Šifra: 10263
Kategorija prozivoda: Skeneri
Proizvođač: Martin




Cena: 106.800,00 rsd

Tech Specs

PhysicalLength:447 mm (17.6 in.)
Width:500 mm (19.7 in.)
Height:195 mm (7.7 in.)
Weight:9.3 kg (20.5 lbs.) including bracket
Dynamic EffectsMotorized rotating parabolic mirror dish
Motorized mirror drum:180° pan (swivel) and 360° tilt (continuous rotation)
Color / animation wheel:7 colors plus 2 x open, twinkle animation effect
Gobo wheel:13 gobos + open, wheel scrolling and continuous rotation, shake effect
Shutter:0 - 100% continuous dimming, variable & random strobe & pulse effects, instant open & blackout
Pre-programmed effects:Full range of macro effects
Control and ProgrammingControl options:DMX, stand-alone, master/slave
DMX channels:10
Stand-alone trigger options:Music trig, auto trig
Music trig also settable via DMX
Setting and addressing:Control panel with backlit LCD display
Protocol:USITT DMX512/1990
Firmware update:Serial upload via DMX link
LampType:130 W short-arc discharge with reflector
Color temperature:8800 K
Average lifetime:6000 hours*
*Manufacturer's figure
OpticsManual focus:2 m - 20 m (6 ft. 7 in. - 65 ft. 8 in.)
ConstructionHousing:High-impact flame-retardant thermoplastic
Color(s):Black
Protection rating:IP20
InstallationMounting points:Adjustable bracket
Orientation:Any
Location:Indoor use only, must be fastened to surface or structure
Minimum distance to illuminated surfaces:0.5 m (19.7 in.)
Minimum distance to combustible materials:0.3 m (11.9 in.)
Minimum clearance around fan and air vents:0.3 m (11.9 in.)
ConnectionsAC power in/thru:Neutrik PowerCon
DMX data in/out:5-pin locking XLR
ElectricalAC power:100-240 V nominal, 50/60 Hz
Typical total power consumption:200 W
Power consumption figures are typical, not maximum. Allow for +/-10% variation.

Typical Power and Current110 V, 60 Hz:1.9 A, 200 W, PF 0.99
230 V, 50 Hz:0.9 A, 196 W, PF 0.95
Measurements made at nominal voltage with all LEDs at full intensity. Allow for a deviation of +/- 10%.
ThermalCooling:Forced air (temperature-regulated, low noise)
Maximum ambient temperature (Ta max.):40° C (104° F)
Minimum ambient temperature:0° C (32° F)
Total heat dissipation (calculated, +/- 10%):685 BTU/hr.
ApprovalsEU safety:EN 60598-2-17 (EN 60598-1), EN 62471, EN 62493
EU EMC:EN 55015, EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3, EN 61547
US safety:UL 1573
US EMC:FCC Part 15 Class A
Canadian safety:CSA C22.2 No. 166
Canadian EMC:ICES-003 Class A
Australia/NZ:C-TICK N4241



Included ItemsLamp (installed)
Mounting bracket
Power cable, 1.5 m, without mains plug
AccessoriesCables, 16 A, for connection to power in chains
Power input cable, 14 AWG, SJT, 1.5 mm2, H05VV-F, with PowerCon input connector, 3 m (9 ft. 11 in.): P/N 11541508
Power relay cable, 14 AWG, SJT, 1.5 mm2, H05VV-F, with PowerCon input connector, 1.4 m (4 ft. 8 in.): P/N 11541509
Power relay cable, 14 AWG, SJT, 1.5 mm2, H05VV-F, with PowerCon input connector, 2.25 m (7 ft. 5 in.): P/N 11541510
Power relay cable, 14 AWG, SJT, 1.5 mm2, H05VV-F, with PowerCon input connector, 3.25 m (10 ft. 8 in.):P/N 11541511
Power connectors
Neutrik PowerCon NAC3FCA power input connector, cable mount, blue:P/N 05342804
Neutrik PowerCon NAC3FCB power output connector, cable mount, light grey:P/N 05342805
Installation hardware
G-clamp:P/N 91602003
Half-coupler clamp:P/N 91602005
DMX termination plug, 3-pin male XLR:P/N 91613017
5-pin male XLR to 3-pin female XLR adaptor:P/N 11820005
Safety cable, safe working load 50 kg (110.3 lbs.):P/N 91604003
Related ItemsRUSH Software Uploader 1™:P/N 91611399
Ordering InformationRUSH Wizard™ in cardboard box:P/N 90480070

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.